


$\mathfrak{U}_s$ 

Ė ɔ ɔ ɔ χ	18V DC	ĥ 32V DC	
Ŧ Ä Ĩ Ǻ χ	1.5W e	24V й	ж
Ѓ Ƴ 3 ^N χ	3	0kΩ	ĥ 10kΩ
Ѓ. 3 ^N χ	4 ĥ	20mA	
Ы Ɔ Ɔ 3 χ	R _L ≤ 500Ω		
Ѓ Ǻ 4 Ÿ χ	± 0.1%F.S.		
□ Ÿ ⅄ χ	0.01%F.S./ 1		
ϥ Ƴ H Ѓ χ	≤ 1s		
Ɔ. ⅃ Ɔ χ	IEC 61326-3-1		
Ɔ ɔ Ä Ÿ χ	≥ 2500V AC e		ж
	≥ 500V AC e		ж
⅃ ⅃ ɔ Ǻ χ	≥ 100MΩ e	/ /	ж
Ŧ Ä □ Ÿ χ	-20 ⅃ ĥ +60 ⅃		
Ѓ Ė □ Ÿ χ	-40 ⅃ ĥ +80 ⅃		
hŦ ð ⅃ χ	15.8mm×	121.6mm×	104.8mm
Ѓ. † ð χ			й
	й		
	e	й	0V/mA ж
		110% e	0mA~2
	0mA й		22m
Z ⅃ ⅃ ⅃ A χ	й	0 Ж1	Ж2

II C ш Т4 й Т6

* 4 8-, 9+; 11-, 12+.

(NEPSI)

ч [Ex ia Ga] II C
(Um) ч 250V
ч (1Ж2Ж3

U ₀ =7.3V,	I ₀ =27mA,	P ₀ =50mW
II C X Co=12μF		Lo=28mH
II B X Co=151μF		Lo=84mH
II A X Co=700μF		Lo=224mH

hannah n